

# REALWOOD

ENGINEERED HARDWOOD FLOORING

## DATA SHEET



### SPECIFICATIONS:

**Species:**

Euro Oak Unfinished

**Thickness:**

15mm (4mm Wear layer)

**Width:**

220 & 260mm

**Length:**

2.2m Segmented

**Coverage:**

220mm Wide – 2.90m<sup>2</sup> / box

260mm Wide – 3.43m<sup>2</sup> / box

**Warranty:**

25 Years Finish / Residential

### ACCESSORIES:

**Skirting:**

120mm X 20mm, 2.4m (Solid Euro Oak)

**T-Mold:**

50mm X 15mm, 2.4m (Solid Euro Oak)

**Stair Nose:**

88.9mm Wide X 22mm thick tongue & Groove, 2.4m (Solid Euro Oak)



### IMPORTANT NOTES:

- VERY IMPORTANT! Flooring should be stored at the job site for a minimum of 48 hours prior to installation for acclimation. Flooring must be properly acclimated to temperature and humidity conditions prior to installation.
- Installation may only occur when the external envelope is completely sealed, all wet works are completed and air conditioning has been installed and operational, maintaining a consistent room temperature at 15-26°C and a constant relative humidity of 25-60%.
- When ordering, 5-10% must be added to the actual square meters needed for grading and cutting allowances
- Not for installation in full bathrooms or high moisture areas.
- This is an unfinished product and will require a hardwax oil coating such as Rubio Monocoat Oil Plus 2C which protects and colours the wood surface.
- After applying the coating as per manufacturer instructions, drying time is 12-24 hours and curing time is 5 days.

Please contact us should any further information be required.

\* The warranty is limited solely to the product as supplied. No warranty is provided for installation, workmanship, or performance resulting from methods of application.

[supertecceilings.co.za](http://supertecceilings.co.za)